



### Features and Benefits

Frequency range: 15-2100MHz  
Output: CML  
Supply voltage: 3.3V  
Current: 90mA Max.  
Frequency stability vs. temperature:  $\pm 25$ PPM  
Operating temperature: -20°C to +70°C  
Size: 2.5x2x1mm  
Package type: SMD




### Typical Applications


Defense Systems  
Mobile Radar Station  
Gigabit Ethernet, SONET/SDH  
Server & Storage, Data Center  
SD/HD Video, FPGA Clock Generation

### Mechanical Drawing & Pin Connections

**Drawing No:** MD240070-1



PIN	Function
#1	Control Voltage
#2	OE
#3	GND
#4	OUTPUT
#5	OUTPUT_N
#6	Supply Voltage



Please keep the middle area blank.  
Do not layout any lines in this space.  
To ensure optimal oscillator performance, place a by-pass capacitor of 0.1µF as close to the part as possible between Vcc and GND pads

Unit in mm  
1mm = 0.0394 inches



**Specifications**

Oscillator Specification	Sym	Condition	Value			Unit	Note	
			Min.	Typ.	Max.			
Operational Frequency	f <sub>0</sub>		15		2100	MHz		
<b>RF Output</b>								
Output Waveform			CML					
Output Level		Output high	V <sub>cc</sub> -0.085		V <sub>cc</sub>	V		
		Output low	V <sub>cc</sub> -0.6		V <sub>cc</sub> -0.32	V		
Duty Cycle			45		55	%		
Rise & Fall Time					0.35	ns		
Startup Time					8	ms		
Tri-State (Input to Pin2)		Enable	0.7 V <sub>cc</sub>			V		
		Disable			0.3 V <sub>cc</sub>	V		
<b>Power Supply</b>								
Voltage	V <sub>cc</sub>	±10%		3.3		V		
Supply Current		V <sub>cc</sub> =3.3V			90	mA		
Stand by Current		V <sub>cc</sub> =3.3V			90	mA		
<b>Control Voltage</b>								
Control Voltage	V <sub>c</sub>	V <sub>cc</sub> =3.3V	0.3	1.65	3	V		
Pulling Range			±50		±250	ppm		
Linearity					±10	%		
Modulation Bandwidth			5		20	KHz		
V <sub>c</sub> Input Impedance			5			Mohm		
<b>Frequency Stability</b>								
Versus Temperature					±25	ppm		
Phase Noise At V <sub>cc</sub> =3.3V, 805.664MHz Frequency		1KHz		-107		dBc/Hz		
		10KHz		-117				
		100KHz		-125				
		1MHz		-135				
RMS Phase Jitter		Integrated 12KHz-20MHz	150		300	fs		
Period Jitter					50	ps		
<b>Environmental Conditions</b>								
Operating temperature range			-20°C to +70°C					