

Dynamic Engineers Inc.

Website: www.DynamicEngineers.com
Email: lnquiry@DynamicEngineers.com

VCXO3225BM-LJ_HCSL-132

Low Jitter VCXO_Voltage Controlled Crystal Oscillator

Features and Benefits

Frequency range: 15-700MHz Output waveform: HCSL Supply voltage: 2.5V Current: 80mA Max.

Frequency stability vs. temperature: ±50PPM Operating temperature: -10°C to +60°C

Size: 3.2x2.5x1mm

Package type: Surface Mount



Typical Applications

Defense Systems
Mobile Radar Station
Gigabit Ethernet, SONET/SDH
Server & Storage, Data Center
SD/HD Video, FPGA Clock Generation


Description


VCXO3225BM-LJ_HCSL-132 is the high frequency and low jitter differential VCXO. It can be widely used in digital circuits.


Mechanical Drawing & Pin Connections

Drawing No: M


MD240085-1







PIN	Function				
#1	Control Voltage				
#2	OE				
#3	GND				
#4	OUTPUT				
#5	OUTPUT_N				
#6	Supply Voltage				



Do not layout any lines in this space. To ensure optimal oscillator performance, place a by-pass capacitor of $0.1\mu F$ as close to the part as possible between Vcc and GND pads

Unit in mm 1mm = 0.0394 inches



Dynamic Engineers Inc.

Website: www.DynamicEngineers.com
Email: lnquiry@DynamicEngineers.com

VCXO3225BM-LJ_HCSL-132

Low Jitter VCXO_Voltage Controlled Crystal Oscillator

Specifications

Oscillator Specification	Sym	Condition	Value			Unit	Note
			Min.	Тур.	Max.		
Operational Frequency	f_0		15		700	MHz	
RF Output							
Output Waveform				HCSL			
Output Level		Output high	0.66		1.15	V	
		Output low	0		0.15	V	
Duty Cycle			45		55	%	
Rise & Fall Time					0.35	ns	
Startup Time					8	ms	
Tri-State		Enable	$0.7~V_{cc}$			V	
(Input to Pin2)		Disable			0.3 V _{cc}	V	
Power Supply							
Voltage	V_{cc}	±10%		2.5		V	
Supply Current		V _{cc} =2.5V			80	mA	
Stand by Current		V _{cc} =2.5V			80	mA	
Control Voltage							
Control Voltage		V _{cc} =2.5V	0.25	1.25	2.25	V	
Pulling Range			±50		±250	ppm	
Linearity					±10	%	
Modulation Bandwidth			5		20	KHz	
VC Input Impedance			5			Mohm	
Frequency Stability							
Versus Temperature					±50	ppm	
Phase Noise At V_{∞} =3.3 V , 805.664MHz Frequency		1KHz		-107		- dBc/Hz	
		10KHz		-117			
		100KHz		-125			
		1MHz		-135			
RMS Phase Jitter		Integrated 12KHz-20MHz	150		300	fs	
Period Jitter					50	ps	
Environmental Condition							
Operating temperature ra	nge	-10°C to +60°C					