

## Dynamic Engineers Inc.

Website: <a href="http://www.DynamicEngineers.com">www.DynamicEngineers.com</a> Email: <a href="http://www.DynamicEngineers.com">http://www.DynamicEngineers.com</a> VCXO3225BM-LJ\_HCSL-331 Low Jitter VCXO\_Voltage Controlled Crystal Oscillator

## **Features and Benefits**

Frequency range: 15-700MHz Output waveform: HCSL Supply voltage: 1.8V Current: 70mA Max. Frequency stability vs. temperature: ±50PPM Operating temperature: -40°C to +85°C Size: 3.2x2.5x1mm Package type: Surface Mount



### **Typical Applications**

Defense Systems Mobile Radar Station Gigabit Ethernet, SONET/SDH Server & Storage, Data Center SD/HD Video, FPGA Clock Generation


#### **Description**


VCXO3225BM-LJ\_HCSL-331 is the high frequency and low jitter differential VCXO. It can be widely used in digital circuits.


## **Mechanical Drawing & Pin Connections**





GND











Please keep the middle area blank. Do not layout any lines in this space. To ensure optimal oscillator performance, place a by-pass capacitor of  $0.1\mu F$  as close to the part as possible between Vcc and GND pads

Unit in mm 1 1mm = 0.0394 inches

Dynamic Engineers, Inc.

Rev. 1

Dynamic Engineers reserves the right to make changes to the company datasheet(s) along with other information contained inside, such as data tables and araphs without notification to potential customers who may have earlier revisions in their possession.



# Dynamic Engineers Inc.

Website: <u>www.DynamicEngineers.com</u> Email: <u>Inquiry@DynamicEngineers.com</u>

## **Specifications**

Oscillator Specification	Sym	Condition	Value			Unit	Note
			Min.	Тур.	Max.		
Operational Frequency	f <sub>0</sub>		15		700	MHz	
RF Output							
Output Waveform				HCSL			
Output Level		Output high	0.66		1.15	V	
		Output low	0		0.15	V	
Duty Cycle			45		55	%	
Rise & Fall Time					0.35	ns	
Startup Time					8	ms	
Tri-State		Enable	$0.7 V_{cc}$			V	
(Input to Pin2)		Disable			0.3 V <sub>cc</sub>	V	
Power Supply							
Voltage	Vcc	±10%		1.8		V	
Supply Current		V <sub>cc</sub> =1.8V			70	mA	
Stand by Current		V <sub>cc</sub> =1.8V			70	mA	
Control Voltage							
Control Voltage		V <sub>cc</sub> =1.8V	0.18	0.9	1.62	V	
Pulling Range			±50		±250	ppm	
Linearity					±10	%	
Modulation Bandwidth			5		20	KHz	
VC Input Impedance			5			Mohm	
Frequency Stability							
Versus Temperature					±50	ppm	
Phase Noise At Vcc=3.3V, 805.664MHz Frequency		1KHz		-107		dBc/Hz –	
		10KHz		-117			
		100KHz		-125		UDC/112	
		1MHz		-135			
RMS Phase Jitter		Integrated 12KHz-20MHz	150		300	fs	
Period Jitter					50	ps	
Environmental Conditio							
Operating temperature ra	nge	-40°C to +85°C					